

EasyOne Pro LAB

The portable solution that offers the broadest spectrum of lung function testing in the GP's office, clinic and hospital

Spirometry Single Breath CO Diffusion Multiple Breath Nitrogen Washout for Lung Volumes and Ventilation Inhomogeneity

The proven ultrasound technology
ndd TrueFlow
ndd MolMass

no calibration, no warm-up time, no moving parts

Automated user guidance throughout maneuvers based on current ATS/ERS standards

Z-score, LLN and %predicted for fast interpretation of results

Reproducible results ensure comparability in multicenter studies

Real-time curves and pediatric incentives

Immediate test quality feedback in accordance with ATS/ERS criteria

Export of pdf files and raw data

Flexible HL7 and XML interface for easy EMR integration
Only 1 gas for DLCO and 1 gas for MBW testing, no calibration gas required

Absolute hygienic solution with Spirette and Barriette consumables eliminates the risk of cross-contamination

Compact device with smooth surfaces for easy and thorough cleaning

TrueFlow
makes the difference

MolMass
the next step

The original ultrasonic flow measurement is highly accurate in all flow ranges, independent of gas composition, pressure, temperature and humidity and does not require calibration during its life-time. The sensor is never in direct contact with the patient's flow. ndd TrueFlow is a hygienic and resistance-free solution.

ndd's molar mass measurement facilitates accurate gas analysis simultaneous with the precise ultrasonic flow measurement. This unique feature allows for a number of applications with new diagnostic possibilities.

ndd
new diagnostic design



Standards & Recommendations

Quality, Medical Devices & Electrical

EN ISO 9001, EN ISO 13485, EN ISO 14971, EN 62366, EN 62304, EN ISO 26782, EN ISO 23747, EN IEC 60601-1, EN IEC 60601-1-2

FDA

510(k) market clearance

MDD 93/42/EEC

CE marked

Associations & Institutes

ATS/ERS 2005, NIOSH/ OSHA, SSA Disability

Languages

English, Dutch, French, German, Italian, Portuguese, Brazilian Portuguese, Russian, Spanish, Swedish, Turkish, Vietnamese

Gas specification

DLCO

10% helium, ± 10%
0.3% carbon monoxide, ± 10%
18 to 25% oxygen (normally 21%)
balance nitrogen

MBW

Oxygen for hospital use

Technical

Printing options

PCL standard, direct to printer or over network

Data management

EasyWare Pro (SQLite, MS SQL Server)

Export/EMR

HL7, XML, GDT, via USB, LAN Network

Hardware Interface

Ethernet port, USB, possibility to upgrade to WLAN

No. of tests

> 10'000 tests

Age range

Spirometry > 4 years, DLCO > 6 years, MBW > 4 years or > 18 kg

Dimensions

27 X 33.5 X 27 cm³ (H x W x D), 8 kg

Device classification

Protection class I
Type BF applied part

Operating conditions

Temp 10-40 °C / 50-104 °F
Rel. Humidity 30-75%,
no condensation
Atmosph. Pressure 620 - 1060 hPa

Power Consumption

50 VA

Parameters

FVC	ATI, BEV, EOTV, FEF10, FEF25, FEF 2575, FEF2575_6, FEF40, FEF50, FEF50/FVC, FEF50/VCmax, FEF60, FEF75, FEF75-85, FEF80, FET, FET25-75, FEV.25, FEV.5, FEV.5/FVC, FEV.75, FEV.75/FEV6, FEV.75/FVC, FEV.75/VCmax, FEV1, FEV1/FEV6, FEV1/FVC, FEV1/FVC6, FEV1/VCmax, FEV1/VCext, FEV3/FVC, FEV3/VCmax, FEV3, FEV6, FVC, FVC6, MEF20, MEF25, MEF40, MEF50, MEF60, MEF75, MMEF, MTC1, MTC2, MTC3, MTCA, PEF, PEFT, to, VCext, VCmax
FVL	ATI, BEV, CVI, E50/150, EOTV, FEF10, FEF25, FEF 2575, FEF2575_6, FEF40, FEF50, FEF50/FVC, FEF50/VCmax, FEF60, FEF75, FEF75-85, FEF80, FET, FET25-75, FEV.25, FEV.5, FEV.5/FVC, FEV.75, FEV.75/FEV6, FEV.75/FVC, FEV.75/VCmax, FEV1, FEV1/FEV6, FEV1/FIV1, FEV1/FVC, FEV1/VCmax, FEV1/VCext, FEV3/FVC, FEV3/VCmax, FEV3, FEV6, FIV25, FIF50, FIF50/FEF50, FIF75, FIV.25, FIV.5, FIV1, FIVC, FVC, MEF20, MEF25, MEF40, MEF50, MEF60, MEF75, MEF90, MIF25, MIF50, MIF75, MMEF, MTC1, MTC2, MTC3, MTCA, PEF, PEFT, to, VCext, VCmax
SVC	ERV, IC, IRV, Rf, VC, VCex, VCext, VCin, VCmax, VT
MVV	MVV, MVV6, MVVtime, VT
DLCO	BHT, COHb, ColBarVol, CO Conc, HE Conc, O2 Conc, Anatomic Dead Space, System Dead Space, Discard Volume, DLadj, DLadj/VA, DLCO, DLCO/VA (KCO), FA CO, FA HE, FE CO, FEV1/FVC, FI CO, FI HE, FRC sb, FRC Cor, Hb, tl, Kroghs K, PAO2, RV sb, RV Cor, RV/TLC, RV/TLC Cor, TLC sb, TLC Cor, TLCO, VA sb, VA Cor, VCext, VCmax, Vd, VI
MBW	CEV, CEV5, Anatomic Dead Space, Syst Dead Space, ERV, FRC base, FRC extrapol, FRC mb, IRV, LCI, LCI5, MO, MR1, MR2, RV mb, RV/TLC mb, TLC mb, VA mb, VC, VCex, VCin, Vd, VT, VT/FRC mb, VT/kg

Predicted normal values Spirometry

GLI	Stanojevic 2009, Quanjer 2012
North America	NHANES III (Hankinson) 1999, Knudson 1983, Knudson 1976, Crapo 1981, Morris 1971 & 1976, Hsu 1979, Dockery (Harvard) 1993, Polgar 1971, Gutierrez (Canada) 2004, Eigen 2001
Latin America	Pereira 1992, Perreira 2006 & 2008, Pérez-Padilla (PLATINO) 2006, Pérez-Padilla (Mexico) 2001, Pérez-Padilla (Mexico, Pediatrics) 2003, Chile 2010, Chile (Pediatrics) 1997
Europe	ERS (ECCS, EGKS, Quanjer) 1993, Zapletal 1977, Zapletal 2003, Rosenthal 1993, Austria 1988, Austria 1994, Sapaldia (Switzerland) 1996, Roca (Spain, SEPAR) 1982, Garcia-Rio (SEPAR) 2013, Vilozni 2005, Falaschetti 2004, Klement (Russia) 1986
Europe Scandinavia	Hedenström 1985 & 1986, Gulsvik (Norway) 1985, Berglund Birath (Sweden) 1963, Langhammer (Norway) 2001, Finnish 1982 (1998), Nystad 2002
Australia	Hibbert 1989, Gore Crockett 1995
Asia	Chhabra (India) 2014, Dejsomitrutai (Thailand) 2000, Indonesia 1992, IP (China, HongKong) 2000 & 2006, JRS 2001 & 2014
Africa	Ethiopia 1985

Predicted normal values DLCO

North America	Ayers 1975, Burrows 1961, Crapo 1981 & 1982, Goldman Becklake 1958, Knudson 1987, McGrath Thompson 1959, Miller 1980, Gutierrez (Canada) 2004, NHANES (Neas) 1996, Polgar 1971
Latin America	Vazquez Garcia (ALAT) 2016
Europe	ERS (Quanjer) 1993, Zapletal 1977, Roca 1990 & 1998, Hedenström 1985 & 1986, Gulsvik 1992, Klement (Russia) 1986
Other	Pereira 2008, Thompson 2008, Kim 2012, Chhabra (India) 2015, Ip (China, HongKong) 2007, JRS (Japan) 2001

Predicted normal values MBW

Europe	Verbanck 2012
---------------	---------------

Flow/Volume Sensor	
Type	Ultrasonic transit time
Range	± 16 l/s
Resolution	4 ml/s
Accuracy	±2% or 0,02 l/min
Volume	±2% or 0,050 l
Flow	±2% or 0,020 l/min
PEF	±5% or 5 l/min
MVV	±2% or 0,050 l
Resistance	~0,3 cm H2O/l/s
Sample rate	400 Hz

Gas-Sensor	CO	CO2
Type	Non-dispersive infrared	
Range	0 to 0,35%	0 to 15%
Resolution	0,0001%	0,005 %
Accuracy	≤ 0,001%	± 0,05% (von 0 bis 5%)
Tracer Gas Sensor	Helium	N2
Type	Ultrasonic transit time	
Range	0 to 50%	0 to 100%
Resolution	0,02%	0,1%
Accuracy	0,05%	0,2%